

## HANGCSILLAPÍTÁSI ÉRTÉKEK

50 mm-s hangcsillapító anyaggal										
	D [mm]	L [mm]	f [Hz]							
			63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz
<b>SAR 100</b>	100	600	10	7	10	17	27	37	29	17
<b>SAR 125</b>	125	600	8	4	9	18	28	35	28	15
<b>SAR 160</b>	160	600	8	5	7	14	24	28	20	15
<b>SAR 200</b>	200	600	10	4	6	12	23	27	15	11
<b>SAR 250</b>	250	600	0	0	0	0	19	20	8	10
<b>SAR 315</b>	315	600	0	1	0	1	17	18	6	8
<b>SAR 100</b>	100	900	5	8	13	26	42	41	32	21
<b>SAR 125</b>	125	900	8	7	11	27	39	38	32	19
<b>SAR 160</b>	160	900	8	8	10	26	32	37	28	18
<b>SAR 200</b>	200	900	3	3	5	26	29	34	20	14
<b>SAR 250</b>	250	900	3	3	3	17	22	33	11	13
<b>SAR 315</b>	315	900	2	4	5	15	22	22	8	8